

EmLED-12NM / EmLED-14NM

EXIT denkolighting.com.sg/emergency-lights/emled-12nm-emled-14nm/

EASI LED Recessed Emergency Light



| With optional big disc



Dimensions (mm)

With big disc adapter



Features and Application

- New compact all-in-one, self-contained LED emergency light for recessed installation on ceilings designed for easy installation and usage.
- Includes an optional big disc adapter.
- Suitable for various indoor environments such as retail, commercial, hospitality and healthcare industries.
- LED lamps provide high efficiency, durability and low energy consumption.



PLS Listed
Emergency
Lighting



Technical Specifications

Mode of Operation

Non-maintained

Lamp	EmLED-12NM: Samsung 2W High flux white LED EmLED-14NM: Samsung 4W high flux white LED
Operating Temperature	ta 0°C ~ 50°C
Mains Supply	230V AC 50Hz/60Hz
Power Consumption	EmLED-12NM: < 1W EmLED-14NM: < 2W
Battery	EmLED-12NM: High temperature NICD battery EmLED-14NM: High temperature NIMH battery
Charger	Fully automatic
Charging Monitor	Green LED
Recharge Period	24 hrs
Testing Facility	Test-switch for independent testing
Emergency Duration	3 hrs
Safety Feature	Low-voltage cut-off to prevent over-discharge of battery
Construction	Polycarbonate
Weight (Nett/Gross)	EmLED-12NM: 0.2 kg / 0.28 kg EmLED-14NM: 0.28 kg / 0.34 kg
Compliance	SS 563-2:2010/A1:2013 SS IEC 60598-2-22:2016 SS IEC 60598-1:2016
Installation	Recessed
IP Rating	IP 20
Warranty	1 year

Ordering Information

MODEL	LAMP	DATASHEET
EmLED-12NM	Samsung 2W high flux white LED	PDF
EmLED-14NM	Samsung 4W high flux white LED	PDF